

## TYPE 1 AGGREGATE

### PRODUCT INFORMATION SHEET

Recycled aggregate 45mm down to dust particle size

#### Description:

Type 1 recycled is an excellent alternative to the more expensive Type 1 limestone product. Our recycled Type 1 is often chosen by contractors for use in road and path construction.

#### Source:

The mixture may contain some or only recycled materials, but not from a single source: not more than 25% of the content may be glass and not more than 50% asphalt. Wood, plastic and metal are inevitable components of demolition waste, but they must be less than 1% of the overall mix.

#### Common uses of Type 1:

In general, applications without any processing include:

- bank protection
- general bulk fills
- base or fill for drainage structures
- capping layer
- road construction
- noise barriers and embankments
- oversite fill



*An example of our recycled Type 1 aggregate*

#### Sustainability:

Produced from construction and demolition waste, this product offers a number of environmental benefits including:

- appeals to environmentally conscious customers
- reduces CO<sub>2</sub> production compared to mined aggregates
- contributes towards requirement for 'materials with recycled content' in construction projects

Customers can be confident of a secure and reliable supply. The material distributed by REMONDIS is produced at our Bedlington Recycling Centre in Northumberland, using modern plant machinery that is expertly maintained and operated.

A testing plan and frequency regime is in place to ensure that our recycled aggregate is tested to meet BS EN 13242 and BS EN 12620 and also conforms to the relevant specifications from those standards. We also fully comply with the WRAP Quality Protocol. Our aggregates are tested by independent UKAS accredited laboratories.



Stephenson Way  
Barrington Industrial Estate  
NE22 7DL

T. 08000 665 550  
E. [sales@remondis.co.uk](mailto:sales@remondis.co.uk)  
W. [www.remondis-jbt.com](http://www.remondis-jbt.com)